

## DS-K5603T-Z Face Recognition Terminal

DS-K5603T-Z Face Recognition Terminal adopts deep learning algorithm, which helps to recognize the face faster and more accurate. It also supports multiple authentication modes: 1:N face picture match, etc. When installed on the swing barrier, it can be applied in scenarios, such as buildings, businesses, financial industries, and other important areas.



### Available Model

DS-K5603T-Z

### Features

- Compatible with Hikvision swing barrier
- Compatible with third-party turnstile via RS-232 interface, RS-485 to Wiegand module, or I/O output module is available
- Water-proof
- 10.1-inch LCD touch screen
- Screen ratio: 16:9; screen resolution: 1280p × 800p
- 2 MP wide-angle dual lens
- WDR
- Adjustable supplement light brightness
- Face recognition distance: 0.3 m to 1 m; Suggested person height for recognition: 1.4 m to 1.9 m
- High performance processor with deep learning algorithm
- Max. 50,000 face pictures storage
- Multiple authentication modes: authentication by comparing face picture, by custom mode, etc.
- Accurate and fast face recognition function
- Apply face picture data to the device via TCP/IP or uploading it to the device via the USB flash drive
- Stand-alone operation
- Transmit and save the comparison results and the captured face pictures to the client software or others
- Apply blacklist from the client software or others to the device or imports blacklist to the device directly.



- Transmit the blacklist comparing results to the client software or others.
  - Device management, log search, and parameter settings via the device.
  - Transfer data (face pictures and blacklist) between the USB flash drive and the device
  - RS-485 communication mode
  - Connect to access controller via RS-232 communication
  - Voice prompts
  - Watchdog design for protecting the device and ensuring device running properly
- \* **Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes.**

## Specifications

Model	DS-K5603T-Z
Processor	GPU
Operation	Embedded Linux system
LCD screen	10.1-inch LCD touch screen; Ratio: 16:9; Resolution: 1280p × 800p
1:1 face recognition duration	≤ 1 s/Person
1:N face recognition duration	≤ 0.5 s/Person
Face recognition accuracy rate	0.3 m to 1 m
Face picture capacity	50,000; JPG and JPEG format
Event capacity	50,000
Communication mode	10/100/1000 Mbps self-adaptive network interface
Interface (built-in)	LAN × 2, RS-232 × 1, RS-485 × 1, USB × 2, HDMI × 1
Camera	2 MP dual-lens camera; 1080p; Suggested person recognition height: 140 cm to 190 cm
Loudspeaker	Loudspeakers × 2
Power supply	12 VDC/3 A (without adapter; centralized power supply); 36W
Working temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Working humidity	0% to 90% (non condensing)
Dimensions	520 mm × 198 mm × 66 mm (20.47" × 7.80" × 2.60")
Protection level	IP55
Application situation	Indoor; outdoor

## Accessory



**DS-KAB5603**

Distributed by



## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikla.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
sateru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com